

▶ VIT'O

Fall arrest safety harness



Technical specifications

Common features NUS67, NUS77A & NUS87A:

- Validated by tests at 140 kg.
- "D" dorsal attachment fitted with a 300 mm length extension strap.
- 44 mm water-repellent polyester main straps (R_≥25 kN).
- Plasticized belt backrest for easy cleaning.
- Automatic aluminium buckles.
- Fall indicator triggered from 300 daN.
- Large polypropylene backplate.
- Comfort pads on the thighs.
- Static resistance on rope > 15 kN.
- Weight: 1.2 kg.
- 3 sizes available (S, M or XL).
- Complies with standards EN361 & EN1497.
- Made in France, a guarantee of quality and short deadlines.

▶ NUS67

- Straps adjustments by male / female quick buckles in black epoxy finish steel.
- Sternal attachment point by connecting strap rings also used for rescue operations (NUS67).

▶ NUS77A

- Adjustments of the straps from below using the male / female quick buckles in black epoxy finish steel
- 44 mm on chest strap with automatic sternal buckles

▶ NUS87A

- Adjustments of the straps from below using the male / female quick buckles in black epoxy finish steel.
- 44 mm on chest strap with automatic sternal buckles.
- 44 mm elastic shoulder strap.

Product description

The **VIT'O fall arrest safety harness** combines performance, comfort, and lightness. It easily adapts to all body types thanks to its high-performance adjustment and locking systems. The straps are adjusted from the top. The automatic buckles ensure that the thigh straps and the on-chest strap are correctly adjusted.

The **VIT'O** complies with 2 standards: the EN361 (Personal Protective Equipment against falls from a height) and the EN1497 (Personal Protective Equipment against falls with rescue loops).

The **VIT'O** is available in 3 versions. Many options are available to make it more practical and comfortable:

- **NUS67:** VIT'O fall arrest safety harness basic version.
- **NUS77A:** version with adjustment of the straps from below. The sternal fall arrest point evolves and is made of an aluminium ring for an easier connection.
- **NUS87A:** version with adjustment of the straps from below, sternal fall arrest point with aluminium ring, and elastic shoulder straps.

Available options

▶ Removable work positioning belt

Intended for all types of maintenance and restraint work, this comfort belt is rotatable and thus allows the body to pivot without causing the work positioning lanyard into its movement.

▶ Removable comfort backrest

Easy to install using Velcro® straps. Its breathable foam makes it an accessory essential to complete your harness.

- Material: polyester and plastic (breathable).
- Velcro® tape on each shoulder.

▶ Extension strap

Used to extend the dorsal attachment point of the fall arrest harness (on dorsal "D" only).

- Composition: tubular strap, width 20 mm (R_≥ 30 kN).
- Single length: 0.35 m and 0.3 m with lark's head knot.

▶ Removable lanyard holder

It is worn on the shoulder straps of all types of harnesses. Easy to install using Velcro®, the lanyard ensures that the connectors are stored so that the user is not hindered when moving.