

▶ TR82 EPDM

Class 3 Full mask with anti-solvent & anti-scratch lens

Single-cartridges
 EN143 - EN14387



RD 40mm EN148-1 universal filters



The **RD40 EN148-1** filters, light and efficient, have an RD40 connector (standardized DIN thread of 40mm).

They are compatible with half-masks and full-face masks standardized to EN148-1 (all brands).

A very wide range of filter cartridges ranging from P3 filters (solid particles and aerosols) to ABEK2Hg-P3 filters (maximum chemical risks).

Filter type		Reference
Particulate filters	P3	124150000
Gas filters	A2	124200000
	AX	124430000
	K2	124210000
	A2B2	123200000
	A2B2E2K2	123200000
Combined filters	A2-P3	124420000
	AX-P3	124550000
	A2B2-P3	123320000
	A2B2E2K2-P3	124530000
	A2B2E2K2Hg-P3	124540000
	A2-P3 REACTOR	124740000

Description	Reference
TR82 EPDM with anti-solvent & anti-scratch lens	112240000

Product description

The **TR82 EPDM** is a class 3 full face mask with 40mm threaded front connection (EN148-1 compliant) with an anti-solvent and anti-scratch polycarbonate lens. The resistant EPDM elastomer face skirt ensures excellent comfort even in case of prolonged use.

Designed to offer respiratory protection adapted to the used filter type, with an excellent quality / price ratio, the **TR82 EPDM** full face mask is particularly suitable in severe environments such as industrial painting, sandblasting, grinding and all activities using solvents.

Like all air purifying respirators (masks, half-masks, powered ventilation devices), it can only be used in presence of a sufficient oxygen level, over 19%.

▶ The highest safety level

- Class 3 EN136 approved, the highest level of safety.
- Anti-solvent and anti-scratch polycarbonate lens.
- A special internal mask with non-return valves minimizes the carbon dioxide level.
- Misting is prevented by the passage of inspired air inside the panoramic screen.

▶ Comfort of use and safety

- Great ease of use even for long periods without risk of fatigue or stress for the user.
- Molded outer skirt for excellent hold on the face and for most morphology.
- The harness with five attachment points is flexible and adjustable, and has buckles with instant attachment, making the mask easy to put on and take off.
- PVC shoulder strap (neck strap).

Technical specifications

- Class 3 EN136 approved (highest level of safety).
- Standard threaded connection Rd 40x1/7 " EN 148-1 compliant.
- Anti-solvent and anti-scratch polycarbonate lens.
- Face skirt in resistant EPDM elastomer, ensuring excellent comfort even in case of prolonged wear.
- TPE inner half-mask with 2 valves for better air circulation which prevents fogging.
- Connection group including the expiratory diaphragm, the sound capsule and the inspiration valve in a single housing.
- Weight: approx 580 grams.
- Tested and approved according to the EN 136: 1998 Class 2 standard and directive 89/686 / cee (PPE) compliant.