

▶ TR 2002 CL2

RD DIN40 class 2 respiratory protection mask

Single-cartridges
 EN143 - EN14387



RD 40mm EN148-1 universal filters



The **RD40 EN148-1** filters, light and efficient, have an RD40 connector (standardized DIN thread of 40mm).

They are compatible with half-masks and full-face masks standardized to EN148-1 (all brands).

A very wide range of filter cartridges ranging from P3 filters (solid particles and aerosols) to ABEK2Hg-P3 filters (maximum chemical risks).

Filter type		Reference
Particulate filters	P3	124150000
Gas filters	A2	124200000
	AX	124430000
	K2	124210000
	A2B2	123200000
	A2B2E2K2	123200000
Combined filters	A2-P3	124420000
	AX-P3	124550000
	A2B2-P3	123320000
	A2B2E2K2-P3	124530000
	A2B2E2K2Hg-P3	124540000
	A2-P3 REACTOR	124740000

Description	Reference
TR 2002 CL2 full mask (One size)	113020000

Product description

The **TR 2002 CL2** is a full class 2 respiratory protection mask with a 40mm thread front connector EN148-1 compliant, compatible with all RD DIN40 filter cartridges on the market. Composed of a polycarbonate (PC) lens with a large visual field and a 5-point harness for good fixation, it combines respiratory protection and comfort.

Covering the eyes, nose, mouth and chin and designed to offer respiratory protection adapted to the used filter type, the **TR 2002 CL2** full mask is suitable for all environments combining respiratory and eye protection.

The **TR 2002 CL2** is a very economical class 2 full face mask with an excellent quality / price ratio, particularly suitable for the chemical, pharmaceutical, agro-food, automotive (industrial painting), gas industries, water and phytosanitary treatment, etc.

Like all air purifying respirators (masks, half-masks, PAPR devices), they can only be used in the presence of a sufficient oxygen level, over 19%.

▶ Comfort of use and safety

- A rim with wide edges ensuring comfort and waterproofness.
- Great ease of use even for long periods without risk of fatigue or stress for the user.
- Excellent hold on the face thanks to an anatomical chin bar.
- The harness with five attachment points, is flexible and adjustable, it has buckles with instant attachment, making the mask easy to put on and take off.
- PVC shoulder strap (neck strap) for transporting the mask during breaks.

Technical specifications

- Compact shape mask reducing bulk.
- Standard thread connection Rd 40x1/7" EN 148-1 compliant.
- Polycarbonate (PC) eyepiece with large field of view.
- TPE outer skirt with ergonomic double sealing lip and bellows.
- Inner half-mask in TPE provided with 2 valves for better air circulation which prevents fogging.
- Connection group including, in a single housing, the expiratory diaphragm, the sound capsule and the inspiration valve.
- Weight: approx 580 grams.
- Tested and approved according to the EN 136: 1998 Class 2 and conforms to directive 89/686 / cee (PPE) standards.