

▶ X-plore® 6300

Full Face RD DIN40 respirator mask

Single cartridges
 EN143 - EN14387



RD DIN40 X-plore® filter cartridges series



The RD DIN40 X-plore® filter cartridges series proposes different filter types for any common application. They offer high protection against many toxic substances, from

organic vapors up to radioactive iodine.

Every filter is CE marked in compliance with the EN 14387 and/or EN 143:2000 standards and are individually packed to ensure maximum protection of unused filters.

Cartridge type		Reference
Particle filters	P3	67 38 932
Gas filters	A2	67 38 855
	AX	67 38 863
	K2	67 38 856
	A2B2	67 38 779
	AXB2	67 38 782
	A2B2E2K2	67 38 804
Combined filters	A2-P3	67 38 860
	AX-P3	67 38 862
	A2B2-P3	67 38 783
	A2B2E2K2Hg-P3	67 38 797
	A2B2E2K2HgNOCO20-P3	67 38 814
REACTOR-P3	67 38 871	

Product description

▶ Secure and comfortable fit

The body of the mask is made with durable and skin-friendly EPDM, with double-layer face seal and triple sealing edges that provide a secure and comfortable fit for virtually any face morphology.

▶ Wide field of view

The distortion-free PMMA lens made with Perspex offers a 180° wide angle that ensures a large field of view with excellent panoramic vision.

▶ 5-point harness

The comfortable 5-point harness does not only ensure simple and quick fitting, but due to the wide straps, it also prevents pressure points on the head.

▶ Efficient ventilation system

The efficient ventilation system with a separate inner mask prevents the lens from fogging and ensures good vision.

▶ Versatile operation

The X-plore® 6300 full face mask features an RD40 thread compliant with the EN 1148-1 standard and can be equipped with the complete X-plore® RD40 filter range.

▶ Easy maintenance and logistics

One size fits all, simplifying logistics and stock management. The barcode on the inside simplifies the recording and maintenance of the masks inventory.

▶ X-plore® 6300 specifications

- Compact design for reduced obstruction
- Enlarged field of view thanks to the distortion-free lens and user fitting
- Hypoallergenic mask body made of high-resistance EPDM
- Scratch resistant PMMA lens (*plexiglass*) with 180° field of view
- Internal half-mask channeling expired air for easy release
- Phonic membrane made of ABS for optimized acoustic diffusion
- Standard RD40x1/7" thread according to EN 148-1
- Weight: approx. 500 grams
- EN 136 class 2 (*CE mark*), NIOSH, AS/NZS tested and approved
- Individually packed (*no filter included*)
- Instructions manual with use, maintenance and storage instructions
- Excellent quality / price / performance ratio

Description	Reference
X-plore 6300 panoramic mask (<i>standard size</i>)	R55800