

► X-plore® 9300

Constant flow supplied air respirator system – Airline respirator



Technical specifications

Materials specifications: Antistatic (approved for ATEX zone 1)

Connector: Nickel plated brass

Cover: Nylon 6/6

Standard belt: Polyester

Decontamination belt: Polyester with PTFE coating

Leather belt: leather

Weight: < 0.5 kg

Standard air inlet connector: CEJN 96

Other available connectors (option): Hensen HK, Hensen 3000, Foster, Schreder, Stäubli, Walther

Size (L x H x w): Belt connector system
120 mm x 160 mm x 40 mm

Operating temperature: -30°C to +60°C -10°C to +60°C

Inlet pressure on user: 3 to 10 bar

Flow: 200 to 1,200 L/min

Alert whistle sound volume: > 90 dbA

Required components:

- Dräger X-plore® constant flow facepiece
- Related breathing hose
- Belt

European certifications (EN):

EN 14594:2005

Directive PPE 89/686/CEE

Other certifications:

AS/NZS 1716:2003, section 8

Russia VNIIPO, GOST

Japan JIS

Product description

The X-plore® 9300 airline respirator is designed for usual industrial applications and provides comfortable and reliable respiratory protection. Thanks to features such as the patented safe-flow reducer and the auto-test function, X-plore® 9300 users can enjoy more operating convenience, safety and flexibility.

► Adjustable and appropriate air flow

With an inlet pressure of 3 to 10 bar and a patented air flow reducer, the X-plore® 9300 supplied air respirator system covers a large range of usual industrial applications. This specific function can provide a continuous and sufficient air flow to the user, even in case of external air supply pressure variations. Moreover, these belts feature a secured flow adjustment in order to increase air flow, and as a consequence the comfort of the user.

► A large range of facepieces

Each facepiece available for the X-plore® 8000 supplied air respirator system is fully compatible with the X-plore® 9300 - half-masks, full face masks, hoods and protective visors. Standards or reinforced flexible (optional) hoses also are available and compatible with the X-plore® 9300.

► Cost-effective maintenance

The X-plore® 9300 supplied air system is easy to maintain and the cost of spare parts required to replace contaminated components is reduced. This enables to spare time and money as no particular cleaning is required.



► Facepieces



Standard half-hood

Covers the head and face but leaves uncovered ears. Cost-efficient, designed limited use.

- Hood material: PP/PE – polycarbonate visor
- Available in S/M size (52 to 59 cm) or L/XL size (57 to 64 cm)
- Weight: approx. 145 g



Helmet with visor

Providing head and eyes protection with efficient respiratory protection. The polycarbonate visor is resistant and long-lasting. It can be raised at 90°.

- Helmet material: ABS – polycarbonate visor (32 cm x 16 cm)
- Unique size
- Weight approx. 630 g



Premium half-hood

Ideal for extended use. Stable donning. Reinforced chemical resistance.

- Hood material: PA with PU coating – polycarbonate visor
- Available in S/M size (52 to 59 cm) or L/XL size (57 to 64 cm)
- Weight: approx. 200 g



Respiratory protective half-mask

Combines flexible mask body with a pre-formed nose area for perfect fit, excellent tightness and comfort.

- Material: Silicon (*black*) rigid blue body made of durable plastic
- Available in S/M size (160 g) or M/L size (175 g)



Standard full hood:

complete protection of the head, face and neck. Lightweight material (205 g) and affordable, designed for limited use.

- Hood material: PP/PE – polycarbonate visor
- Available in S/M size (52 to 59 cm) or L/XL size (57 to 64 cm)
- Weight: approx. 205 g



Full face mask

Enlarged field of view related to the visor shape and user face positioning

- Material: resistant and hypoallergenic EPDM – PMMA scratch-resistant visor
- Universal size
- Weight 500 g



Complete Premium hood

complete protection of head, face and neck. Well-suited for extended use. Reinforced chemical resistance.

- Hood material: PA with PU coating – polycarbonate visor
- Available in S/M size (52 to 59 cm) or L/XL size (57 to 64 cm)
- Weight: approx. 390 g



Panoramic mask

Very well designed, ergonomic and available in several sizes, it offers optimal field of view and comfortable and safe adjustment

- Material: resistant and hypoallergenic EPDM
- Available in 3 sizes
- Weight approx. 600 g



Protective visor

Resistant and long-lasting PC visor equipped with a hood that efficiently protects the head from dust.

- Hood material: PA with PU coating – polycarbonate visor (32 cm x 15.5 cm)
- Unique size
- Weight approx. 490 g



Welding helmet mask

High comfort helmet mask with sober and elegant design featuring an auto-darkening ADF 5 to 13 welding filter. For long-term welding applications.

- Filter darkening automatic adjustment: shade range from 9 to 13
- Unique size
- Weight approx. 780 g






► X-plore® 9300

Constant flow supplied air respirator system



The X-plore® 9300 airline respirator is an ideal solution for many industries. Ideal in environments where the correct oxygen rate can't be guaranteed, this supplied air respirator combines the highest level of respiratory protection to an extended use.

Completely modular, the various parts of the system provide an almost unlimited flexibility, allowing users to build a system that perfectly meets their needs

Compressed air supply system

		Designation	Part Number
	System	X-plore 9300 supplied air respirator	33 63 587
		Standard belt size L (<i>large</i>)	33 63 682
		Decontaminable belt size L (<i>large</i>)	33 63 683
		Leather belt size L (<i>large</i>)	33 63 462
		Comfort pad for X-plore 9300	33 63 425
	Hoses	Standard hose for hoods	R 59 620
		Standard hose for helmets and visors	R 59 640
		Flexible hose for hoods	R 59 600
		Flexible hose for helmets and visors	R 59 650
	Hoods	Standard half-hood (<i>size L/XL</i>)	R 59 810
		Premium half-hood (<i>size L/XL</i>)	R 59 850
		Standard full hood (<i>size L/XL</i>)	R 59 830
		Premium full hood (<i>size L/XL</i>)	R 59 870
	Masks and half-masks	X-plore 4740 half-mask (<i>size L/XL</i>)	R 59 870
		X-plore 6300 full face mask	R 55 800
		Panorama standard P mask with bandage	R 54 450
		FPS 700 mask (<i>size L/XL</i>)	R 56 300
	Helmets and visors	Helmet with visor (<i>black</i>)	R 58 325
		Protective visor	R 59 900
		Welding helmet	R 59 920

Air supply

		Désignation	Part Number
	Air supply hoses	3 meters length	33 52 463
		5 meters length	AL 01 260
		10 meters length	AL 01 261
		20 meters length	AL 01 262
		30 meters length	33 52 467
		50 meters length	33 52 468
	Air filter unit	PAS F3000P portable filter unit for 3 users with CEJN connectors (<i>1/4" BSP inlet connector</i>)	33 59 916
		PAS F3000P portable filter unit with pre-filter for 3 users with CEJN connectors (<i>1/4" BSP inlet connector</i>)	33 59 922