

▶ Dräger Alcotest 6000

Professional breathalyzer



Technical specifications

Measurement principle: Dräger Sensor 1/4" electrochemical sensor; specific to alcohol

Measuring range: 0 to 2,5 mg/l ; a message is displayed if measuring range limits are reached

Standard sampling: automatic sampling once the minimum volume or breath time has been reached; Possible passive sampling without mouthpiece or manual initiation of sampling.

Ready for use: approx. 2 s after switching on

Measurements display: environ 3 After approx. 3 s (at 0 mg/L); after approx. 10 s (at 0.5 mg/L, room temperature)

Graphic LCD display: backlit LCD display; 32 x 22 mm (128 x 64 pixels)

LED: 2-colour, to support results display and warning messages

Audible signals: Different signal tones to support display messages and warnings

Data logger: Storage of the last 500 tests with test numbers

Power supply: 1x CR123A battery, On-screen charging status display; a full battery can perform around 1,500 alcohol tests

Mouthpiece adaption: Improved Slide'n'click mouthpiece attachment; can be fitted for right or left orientation

Mouthpiece: hygienic, individually wrapped, secure, with secure air outlet

Housing: ABS/PC shock resistant

Compliance: EN 15964, NHTSA, FDA

Dimensions: About 50/60 x 141 x 31 mm

Weight: about 150g with the battery

Product description

The sophisticated product design of the **Dräger Alcotest 6000** meets the requirements for performing a breath alcohol test quickly, easily and hygienically.

It is also possible to measure alcohol in the ambient air (passive), in which case a mouthpiece isn't required.

The device is ready to use within seconds. The shape of the Slide'n'click mouthpiece allows you to intuitively fit it correctly, even in the dark. The **Dräger Alcotest 6000** is ready to use again immediately after changing the mouthpiece.

Once the mouthpiece is replaced, the **Dräger Alcotest 6000** can be reused immediately.

Slide'n'click mouthpieces

Available in 100, 250, and 1000 mouthpieces packs, with or without one-way valves. One-way valves prevent any crossed contamination.

Dräger Mobile Printer BT

The **Dräger Mobile Printer BT** allows printing from any compatible Dräger test device within 15 meters. Lightweight and compact, the portable printer attaches to your belt with a clip. With its OK button for on and off, and its paper feed button, it is easy to use. Light symbols indicate the status of the unit.

Codification	Description
37 06 961	Dräger Alcotest 6000 standard
68 10 690	100 units package
68 10 825	250 units package
68 10 830	1000 units package
37 00 421	Dräger Mobile Printer

▶ Ethylotest calibration

GazDetect offers a full range of ethanol gas mixtures to meet any requirements for alcohol screening devices and interlock systems.



These mixtures are produced in compliance with current most demanding standards and fits in any handheld equipment and interlock system.