

Promask & Vision

Promask FM3 & Vision FM4 side-fitting masks





Promask FM3 mask

The **Promask FM3** is a class 3 full-face respirator with a 40mm threaded side connector to EN 148-1, compatible with all Rd DIN 40 filter cartridges. Featuring a panoramic lens for a wide field of vision and a 5-point harness for a secure fit, it combines respiratory protection and comfort. The specific internal mask with non-return valves minimizes CO2 levels and fogging.

Designed to offer respiratory protection adapted to the type of filter used, the **Promask FM3** provides excellent value for money and is suitable for all environments involving respiratory and eye protection. Like all filtering respirators, it can only be used when oxygen level is higher than 19%.ead.

► The technical specifications of Promask FM3 mask

- EN 136 class 3 approved (highest level of safety)
- Extended field of vision thanks to eye-piece shape and lateral filter positioning
- Standard Rd40 x 1/7" threaded connection to EN 148-1
- Extremely comfortable to use, even for long periods, without risk of fatigue or stress for the user
- EN 136 class 3 approved (highest level of safety)
- Body in high-strenght halo butyl elastomer
- Heavy-duty polycarbonate (PC) lens with 180° field of vision
- Inner half-mask channels exhale air and facilitate its expulsion to the outside
- Acoustic membrane in ABS material optimizes sound diffusion
- Weight: approx. 525 grams



The **Vision FM4** panoramic mask offers a real eye-catcher regarding visibility (98% field of vision). It's a single-cartridge mask (Rd DIN 40mm EN 148-1 universal threaded connection), with the option of connecting the cartridge to the front (classic) or the side (sideways).

The visor features vertical and horizontal curvature without visual distortion. It is also reinforced in a standard version to ensure resistance to solvents and scratches, with minimal maintenance costs.

► An exceptional field of vision

The Vision FM4 panoramic mask offers best-in-class visual comfort and genuine visual appeal. Available in three sizes and two filter attachment positions, it is designed for a wide range of users. The visor of this panoramic mask ensures an almost total field of vision (98%) and features vertical and horizontal bending without any visual distortion.

The filter is positioned low and close to the face for excellent balance and weight distribution. The face seal is made of LSR (liquid silicone rubber), combining the comfort and flexibility of silicone with resilience and long life. Its design ensures a wide contact zone for an efficient fit without requiring over-tightened harness.

All these features combine to deliver exceptional comfort of use, and the highest level of user acceptance.

► The technical specifications of the Vision FM4 mask

- Approved to EN 136 Class 3 (highest safety level), EN 137:2006 Class II and AS1716N7
- Standard Rd40 x 1/7" threaded connection to EN 148-1
- Exceptional 98% field of view
- Toroidal screen with two distortion-free horizontal and vertical curvatures
- Extremely comfortable to use, even for long periods, without risk of fatigue or stress for the user
- Reinforced visor, resistant to solvents and scratches
- Large sealing lip
- EN 136 Class III certified
- Available with rubber or mesh head harness or with F1 helmet attachments
- Available in 3 sizes: S, M or M/L

Non contractual document. Any reproduction, even partial, is prohibited without prior agreement. © GazDetec