

► NUS65A

Versatile fall arrest harness



Technical characteristics

- Validated by tests at 140 kg.
 - 48 mm wide main straps in polyester ($R \geq 22$ kN).
 - Polypropylene backplate with an anti-fall hook.
 - 25 mm wide on chest strap.
 - Simultaneous adjustment of the straps and thigh straps by male-female quick-release metal buckles in white zinc-plated steel.
 - "D" dorsal attachment fitted with a 300 mm length extension strap.
 - Sternal fall arrest attachment on two webbing loops to be linked together.
 - Padded leg straps with automatic buckle closure.
 - Static resistance on rope > 15 kN.
 - Weight: 1.2 kg.
 - 3 sizes available (S, M or XL).
 - Complies with the EN361 (PPE against falls from a height) & EN1497 standards (PPE against falls from a height with rescue loops).
- Class 3 PPE - such as fall arrest harnesses - correspond to equipment that protects against serious and fatal risks. For obvious reasons of personnel safety, periodic verification of this type of equipment is mandatory and must be carried out at least once a year by an authorized company.

Product description

The **NUS65A** is a versatile fall arrest harness combining performance, comfort, and lightness. Equipped with automatic buckles and padded leg straps, it easily adapts to all body types thanks to its high-performance adjustment and locking systems. It is a harness with 2 attachment points: 1 sternal point on textile buckles and 1 dorsal point on metallic "D".

The **NUS65A**, with its excellent value for money, complies with the EN361 standard (PPE against falls from a height).

It is a French-made product that offers a guarantee of quality, short lead times and compliance with current French and international standards, an undeniable advantage!

Available in 3 sizes (S, M / L & XL) the **NUS65A versatile fall arrest harness** has many options that complement it to make it even more practical and comfortable.

Available options

► Removable work positioning belt

Intended for all types of maintenance and restraint work, this comfort belt is rotatable and thus allows the body to pivot without dragging the work positioning lanyard into its movement.

► Removable comfort backrest

Easy to install using Velcro® straps. Its breathable foam makes it an accessory essential to complete your harness.

- Material: polyester and plastic (breathable).
- Velcro® tape on each shoulder

► Extension lanyard:

Used to extend the dorsal attachment point of the fall arrest harness (on dorsal "D" only).

- Composition: Tubular strap, width 20 mm ($R \geq 30$ kN).
- Single length: 0.35 m and 0.3 m with lark's head knot.

► Removable lanyard holder

It is worn on the shoulder straps of all types of harnesses. Easy to install using Velcro®, it ensures that the connectors are stored so that the user is not hindered when moving.